

MATERIAL SAFETY DATA SHEET
Prepared according to 29 CFR 1910.1200

DATE PREPARED: November 1991
DATE REVISED: February, 2004

PAGE 1
MSDS NO: 144

SECTION I - IDENTIFICATION

L&M CONSTRUCTION CHEMICALS, INC.
14851 CALHOUN ROAD
OMAHA, NE 68152

ASSISTANCE (CHEMTREC) 800-424-9300
EMERGENCY PHONE NO. 402-453-6600

ID NO.: N/Ap

PRODUCT

NAME: **EMERYPLATE FF**

DOT CLASS: N/Ap

CHEMICAL

NAME: Emery Hardener

DOT SHIPPING

NAME: N/Ap

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENTS	OSHA PEL	ACGIH TLV	CAS	% wt
#1: Portland Cement	5 mg/m ³	5 mg/m ³	65997-15-1	30-35
#2: Emery Aggregate	15 mg/m ³	10 mg/m ³	1320-74-5	65-70

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (F): None EMERYPLATE FF is a powdered solid.
VAPOR PRESSURE (mm Hg): None
VAPOR DENSITY (AIR = 1): None
SOLUBILITY IN WATER: Slight
APPEARANCE: Grey Powder
ODOR: Odorless

SPECIFIC GRAVITY (H₂O = 1): 3.0
PERCENT VOLATILE BY VOLUME: None
MELTING POINT: Above 1000°F
BULK DENSITY: N/Ap
PH INFORMATION: N/AP
EVAPORATION RATE: None

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

HAZARDS FIRES: None EMERYPLATE FF is non-combustible.
FLASH POINT, °F, (method used): None
FLAMMABLE LIMITS - LEL: N/Ap UEL: N/Ap

EXTINGUISHING MEDIA: Not required

SPECIAL FIRE FIGHTING PROCEDURES: None

SECTION V - REACTIVITY DATA

STABILITY: unstable: stable: X Keep dry until used.
INCOMPATIBILITY (materials to avoid): None
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None
HAZARDOUS POLYMERIZATION: may occur: will not occur: X
CONDITIONS TO AVOID: None

SECTION VI - HEALTH HAZARD DATA**EMERYPLATE FF**

POTENTIAL EFFECTS OF EXPOSURE (listed by primary routes of entry)

INHALATION: Product contains crystalline cement and emery aggregate. Repeated inhalation of cement in excess of the TLV over extended periods can cause silicosis. Dust may cause coughing, shortness of breath. May also affect breathing capacity.

SKIN: Dryness, itching, rashes and burns can develop following skin contact. Skin abrasions can occur if material is rubbed against skin. Dermatitis and skin sensitization can develop after repeated or prolonged skin contact. Product is not absorbed through skin.

INGESTION: No toxic effects are known to be associated with ingestion of this material.

EYE CONTACT: This material can irritate and may burn eyes following direct contact. The aggregate particles may cause abrasions of the cornea.

EMERGENCY & FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If cough, irritation, difficulty in breathing or other respiratory symptoms persist or develop, consult a physician. Note to physician: mucosal injury following ingestion of this material may contraindicate the induction of vomiting in the treatment of possible ingestion.

SKIN: Rinse skin free of material with water to avoid abrasion of skin. Do not rub until skin is free of material, then wash thoroughly with soap and water. If redness persists, seek medical attention. Remove and decontaminate clothing and footwear before reuse.

INGESTION: Give one to two glasses of water to drink and refer to medical personnel.

EYE CONTACT: Do not rub eyes. Rinse immediately with plenty of water for at least 15 minutes and seek medical assistance.

CARCINOGENICITY OSHA: NO NTP: NO IARC: NO

SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: No hazards. Sweep up and maintain normal housekeeping procedures. If necessary, dike spills of material and shovel into waste containers. Avoid generating dust.

WASTE DISPOSAL METHOD: No hazards. Reuse powder if uncontaminated. Discarded product is non-hazardous waste under RCRA (40 CFR, Part 261). Dispose as non-hazardous waste in compliance with local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: Minimize broken bags and spilled materials by employing good handling procedures. Store in cool, dry area off the ground. Avoid contact with acids and oxidizers. Minimize dust generation. Avoid eye and skin contact. Avoid breathing dust.

OTHER PRECAUTIONS: No applicable information found.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: NIOSH approved particulate mask.

VENTILATION

LOCAL EXHAUST: Use when possible to minimize exposure

PROTECTIVE GLOVES: Recommended

EYE PROTECTION: Safety goggles recommended

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK/HYGIENIC PRACTICES: Decontaminate clothing and footwear before reuse.

END OF MSDS

