

## E Z STRIP™

Concrete Form Release

### MANUFACTURER

L&M Construction Chemicals, Inc.  
14851 Calhoun Road  
Omaha, NE 68152  
Phone: (402)453-6600  
FAX: (402)453-0244  
Website: [www.lmcc.com](http://www.lmcc.com)

### PRODUCT DESCRIPTION

**E Z STRIP** is a VOC-compliant, nonstaining, ready-to-use concrete form release for application to forms for easy stripping. It is a pale, fast drying, sprayable liquid that is non-toxic and economical.

**E Z STRIP** forms a physical barrier to prevent concrete sticking or build-up on forms, equipment and any accessories that come in contact with concrete. The resulting concrete is stain-free and ready to receive paints, penetrating sealers, moistureproofers or other toppings.

**E Z STRIP** contains no diesel fuel or fuel oil.

**E Z STRIP** is a neutral petroleum mineral oil release agent. **E Z STRIP** is non-toxic and complies with local area and state VOC requirements.

**E Z STRIP** is not harmful to concrete surfaces.

**Basic Use:** **E Z STRIP** is ready-to-use and can be applied by spray or other conventional methods. The film resists normal rain wash off. Proper use of **E Z STRIP** insures that forms strip clean, reducing concrete repair and costly form cleanup. The concrete surfaces allow paints and dampproofing asphalt coatings to satisfactorily bond.

### FEATURES & BENEFITS

- Economical release.
- VOC compliant.
- Sprayable.
- Non-residual, non-staining.
- Contains no diesel fuel or fuel oil.
- Apply in sub-freezing temperatures.

### ESTIMATING

**E Z STRIP** is available in 5 gallon (18.9-liter) and 55 gallon (208-liter) containers. Containers are identified with product name and batch code.

#### Approximate Coverage Rates:

Steel, plastic, fiberglass: 600 ft<sup>2</sup>/gallon (15 m<sup>2</sup>/L)  
Wood and paper forms: 400 ft<sup>2</sup>/gallon (10 m<sup>2</sup>/L)  
Pipe plants, block plants, paving equipment: Coat lightly before each use.

### TECHNICAL DATA

#### Applicable Standards:

Corps of Engineers CE 03300  
Bureau of Reclamation.  
VOC compliant.

#### Physical Properties:

Viscosity, ASTM-C-88, 100°F (38°C), SUS ..... 50  
Color Max, ASTM-D-1500 ..... 3  
Flash Point, min, ASTM-D-92 ..... 220°F (104°C)  
Freeze Temperature ..... <20°F (<-28°C)  
Freeze Damage ..... None  
VOC, grams/liter ..... <50

### INSTALLATION

**Surface Preparation:** Form surfaces should be clean and dry. For clean concrete, careful cleaning of form panels to remove all rust, scale, concrete, dirt and existing form oils is essential. Replace damaged and worn forms prior to treatment.

**Applications:** Apply **E Z STRIP** in a uniform manner by sprayer or roller without puddling. A thin coat should be applied prior to each pour for best results.

### FOR BEST RESULTS:

Not recommended for tiltup construction, unsealed plaster or concrete molds, or over forms with standing water. Do not apply in rain. Do not overapply or puddle.

### PRECAUTIONS

Keep out of reach of children. Avoid prolonged contact with skin. Use with adequate ventilation. Do not inhale mist.

Please refer to Product Material Safety Data Sheet (MSDS) before using.

### STORAGE/SHELF LIFE

**E Z STRIP** drums are to be kept tightly closed. If stored outside, place drums on sides to prevent rainwater contamination through bungs. Shelf life is a minimum of two years in unopened containers when properly stored.

### FAX ON DEMAND/WEBSITE

L&M's exclusive Fax On Demand and its convenient internet website offer instant access to Technical Data Sheets, Material Safety Data Sheets, product updates, and other useful information. Simply dial 800-839-9887 or visit [www.lmcc.com](http://www.lmcc.com) and follow the easy steps.



## **LIMITED WARRANTY**

*This product is warranted to be free of defects in material and workmanship, and conform to L&M Construction Chemicals ("L&M") quality control standards. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind, expressed or implied including but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose. Satisfactory results depend upon many factors beyond L&M's control. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from his or her direct use, indirect use or consequential to their use of the product. L&M shall not be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use or inability to use the product. L&M's sole responsibility shall be to replace that portion of the product which proves to be defective. Any warranty claim must be made within six (6) months from the date of the claimed breach. This limited warranty applies only if the product was properly installed and used according to all instructions and was properly stored prior to use.*

**For Professional Use Only.**

©2005, L&M Construction Chemicals, Inc